



## BasicLINE

CLASSIC | PRACTICAL | SMART

# KAA 1300 D automatic spray gun



The KAA 1300 D is primarily used to spray sealants, sealing compounds or PVC. The KAA 1300 D processes highly viscous media efficiently, reliably and in a resource-conserving manner. Its light weight, coupled with a simple design, makes it not only easy to handle but also extremely user-friendly. The KAA 1300 D offers high precision and reproducibility of the coating result – particularly in complex, fully automatic coating systems.

The robust and durable technology ensures low maintenance requirements, as only a small number of components are used.

- Large opening, valve seat 6 mm up to 200 bar
- Smooth material channels
- Easy assembly
- Few components
- Reliable design
- Material-conveying parts optionally available in stainless steel
- Easy-to-clean surfaces
- Durable and robust

### Technical data

#### Measurements and weight

Width: 40 mm  
Height: 40 mm  
Length: 110 mm  
Weight: 310 g

#### Pressures and temperatures:

##### Temperature

Max. material temperature: 50 °C  
Max. temperature of control air: 50 °C

##### Pressures / temperature

Max. material pressure: 200 bar  
Max. material temperature: 50 °C  
Min. control air pressure: 4 bar

##### Connections

Material connection: G 1/4 female  
Control air connection: G 1/8 female